

DECORAZZI ACRYLIC WALL PUTTY

FINECEM ACRYLIC WALL PUTTY

ENVIRONMENTALLY RESPONSIBLE

Decorazzi has its primary concern about physical environment and human health. This is the precise reason we refrain from using added Lead, Mercury, Arsenic & Chromium since inception.



PRODUCT DATA SHEET Product Code: 1050

PRODUCT OVERVIEW

Decorazzi Finecem Acrylic Wall Putty is a water - based putty with alkali resistant acrylic co-polymer to provide a rich smooth finish when applied on masonry interior walls. Its unique design and butter like consistency ensures easy applicability, excellent filling, levelling and sanding properties.

PRODUCT BENEFITS



Durable

Protects expensive paint from dampness, peeling off and flaking, there by avoid frequent repainting.



Value for Money

True colour tone of the paint is maintained. Primer may not be required, hence reduces paint consumption.



Dual Usage

Superior finish of top coats thereby ensures aesthetic look for ceiling, internal and external wall.



Ease of Application

Decorazzi Finecem Acrylic Wall Putty can be applied easily with putty knife or steel trowel on masonry plastered surfaces.

PRODUCT FEATURES



Finish

Smooth and Matte



Water Resistant

This product has excellent water resistance feature



Adhesion

Excellent adhesion to base plaster / concrete



UV Resistant

It has good resistance against harmful UV rays



PACKAGING AND STORAGE

Decorazzi Finecem Cement Wall Putty is available in 25 kg, 20 kg, 10 kg, 5 kg and 1 kg. It has a shelf life of 12 months if stored in a cool and dry location.

As temperature, humidity, water addition and other parameters vary from site to site - this information should be treated as a general guideline.

DIRECTIONS FOR USE

SURFACE PREPARATION

Clean loose particles, dirt, grease and traces of foreign material from the surface, if necessary by using sand paper or by chipping.

For loose plaster areas, remove the defective material and re-plaster the area with proper mixture of plaster.

For ceilings / walls, which are not even, re-plaster it with proper plaster mix to make them even.

Fill up any crack in base plaster by using appropriate crack filler.

MIXING

Take 350 - 400 ml of clean water for 1 Kg of Finecem Acrylic Wall Putty in a clean bucket. It is very important that Finecem Acrylic Wall Putty be added in water and not vice versa.

Stir continuously by using an electric mixer or by hand to obtain a homogeneous lump-free paste.

Allow the resultant paste to stand for about 10 minutes for the additives to dissolve.

Re-mix for about 2 minutes, The mixture paste is now ready to apply.

Use the mix within 30 minutes.

APPLICATION

Dampen the surface to be plastered with clean water. Allow excess water to drain off.

Using a steel trowel / blade, apply the above mix to a thickness of about 0.5 - 1 mm. Level and smoothen the surface and cure the first coat after it dries.

Apply the second coat of 0.5 - 1 mm after the first coat has fully dried and set. In areas of high temperature and low humidity curing for two days is recommended.

The thickness of each coat should not exceed 1 mm and total plaster thickness should not exceed 2 mm.

Smoothen with a steel trowel. Use Sand Paper No. 600, if so desired.

SAFETY FEATURES

- Decorazzi Finecem Acrylic Wall Putty contains only eco-friendly fillers and additives.
- Recommended to keep it out of reach of children.
- May be harmful if swallowed. In case of ingestion, seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Wear suitable gloves. In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not breathe vapour. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation
- Do not pour leftover putty down the drain or in water courses.
- In the event of spills, contain spillage using sand or earth.

PRECAUTIONS

- Best results are obtained when this product is applied at moderate humidity and temperature conditions. Avoid applying below 10°C or at a very low humidity and high temperature. In these conditions performance of putty may get affected.
- Avoid exposure of putty to the atmosphere in order to prevent any kind of slag formation.
- Avoid keeping the putty paste for a long period. It may cause slag formation.
- Do not mix with more water than it is recommended.

Decorazzi Paints and Coatings Pvt. Ltd.

Victoria Park, Level 6, Block - GN, Plot - 37/2, Sector V, Salt Lake City, Kolkata - 700 091

Customer Care No.: +91 33 4057 9000 | E-mail: customercare@decorazzipaints.com

Visit us: www.decorazzipaints.com | Follow us: www.facebook.com/DecorazziPaints | CIN No.: U24290WB2017PTC221056